

# KanexPro EXT-4KFIBERPRO HDMI 2.0 Fiber Optic Extender (Transmitter/Receiver) Kit with 4K/60 up to 300 meters

<b>Transmitter</b>	
Input	(1) HDMI IN
Input Connector	(1) Type-A female HDMI
Output	(2) OPTICAL OUT; (1) AUDIO OUT
Output Connector	(2) LC connector; (1) Toslink connector
Control	(1) IR IN; (1) IR OUT; (1) RS232
Control Connector	(2) 3.5mm mini jacks; (1) 3-pin terminal block
<b>Receiver</b>	
Input	(2) OPTICAL IN; (1) AUDIO IN
Input Connector	(2) LC connector; (1) Toslink connector
Output	(1) HDMI OUT
Output Connector	(1) Type-A female HDMI
Control	(1) IR IN; (1) IR OUT; (1) RS232
Control Connector	(2) 3.5mm mini jacks; (1) 3-pin terminal block
<b>General</b>	
Video Resolution	Up to 4Kx2K 60Hz 4:4:4 HDR
Audio Format	PCM, Dolby Digital, DTS, DTS-HD
HDMI Standard	HDMI 2.0
HDCP Version	HDCP 2.2
Transmission Distance	=300m via single-mode or OM3/OM4 multi-mode fiber cables.
Operation Temperature	-10°C ~ +55°C
Storage Temperature	-25°C ~ +70°C
Relative Humidity	10%-90%
Power Supply	Input: AC 100~240V, 50/60Hz; Output: 12V DC 1A.
Power Consumption	9W (max)
Dimension (W*H*D)	5.10" x 0.78"x 3.30"
Net Weight	0.38 lbs (175g)