

# KanexPro HDMX44-18G 4x4 HDMI 2.0 Matrix Switcher with 4K/60Hz

<b>VideoBandwidth</b>	600MHz/18Gbps
<b>InputPorts</b>	4 x HDMI 1 x IR 1 x RS-232 1 x MiniUSB (Service) 1 xRJ45 (Control)
<b>OutputPorts</b>	4 x HDMI
<b>Supported Resolutions:</b>	480i ~1080p@24/50/60Hz 4K up to 4096x2160@60Hz (YUV 4:4:4,8-bit) PC resolutions: VGA~WUXGA
<b>IR Frequency</b>	30~50kHz
<b>BaudRate</b>	115200bps
<b>PowerSupply</b>	24V DC/2.7A (US/EU standards,CE/FCC/ ULcertified)
<b>ESD Protection</b>	Human body model: ±8 kV (air-gapdischarge) ±4 kV (contactdischarge)
<b>Dimensions</b>	17.0" x 1.7"x 6.2" (436 mm x 44 mm x 160mm WxHxD) [CaseOnly] 17.0" x 1.8" x 6.60" (436 mm x 48 mm x167.5mm WxHxD) [All Inclusive]
<b>Weight</b>	4.55 lbs. (2068g)
<b>Chassis Material</b>	Metal
<b>Color</b>	Black
<b>OperatingTemperature</b>	0°C~40°C/32°F~104 F
<b>Storage Temperature</b>	-20°C~60°C/-4°F~140 F
<b>Relative Humidity</b>	20~90% RH(non-condensing)
<b>PowerConsumption</b>	21 Watts

\* Please check manual under downloads tab for more advanced spec information.