

Soundtube HP129a-BK 12in Hi-Power Coaxial Open-Ceiling Speaker/118Hz-16kHz/Black

| | |
|------------------------------------|--|
| System Type | 12-inch, two-way, high-power, ported (150watt transformer for 70.0/100/25-volt or transformer bypass position) |
| Impedance (nominal): | 8 ohms |
| Sensitivity dB @ 2.83 V/1 m | 97.0 dB |
| Sensitivity dB @ 1 W/1 m * | 97.0 dB |
| Frequency Response (-3 dB) * | 118 Hz-16 kHz |
| Frequency Response (-10 dB) * | 73 Hz-19 kHz |
| Max. Program Power * | 300 W |
| Max. Continuous Power RMSs | 150 W |
| Max. Power SPL @ 1 m 6 | 119.0dB |
| Coverage Angle (-6 dB @ 2 kHz) | 80° |
| Coverage Angle (-6 dB @ 10 kHz) | 90° |
| Coverage Angle (Avg. 2 -10 kHz) | 95° |
| Directivity Factor (Q) | 6.1 (Avg. 100 Hz -10 kHz) 10 (2 kHz) |
| Directivity Index (DI) | 6.6 dB (Avg. 100 Hz -10 kHz); 10 dB (2 kHz) |
| Tap Selector | Five-position rotary switch with transformer bypass position |
| Transducer - Low-Frequency Driver | 305 mm (12 in.) treated fiber cone, treated cloth surround |
| Transducer - High-Frequency Driver | 1 x 35 mm (1.375 in.) Mylar compression driver with waveguide |
| Low Frequency Voice Coil | 50.8 mm (2.00 in.) |
| Crossover Frequency | 2.2 kHz |
| Network Type: Low-Pass | 24 dB per octave. 4th order |
| Network Type: High-Pass | 24 dB per octave. 4th order |
| Enclosure Material | Injection molded ABS baffle, glass fiber reinforced |
| Grille | 61 drite-plated steel with powder-coat finish |
| Inputs | Four-pin, 5.08 mm Euroblock for individual or daisy chan connection |
| Colors | Black or white |
| Height | 452.1 mm (17.8 in.) |
| Diameter | 457.2 mm (18.0 in.) |
| Weight | 16.4 kg (36.0 lb) |
| Shipping Weight | 18.9 kg (41.5 lb) |
| Included accessories | Hanging hardware, Euroblock connector and terminal weather boot |
| Optional accessories | Surface mount bracket (AC-HP-SM129) |
| Packaging | One per box |
| Regulatory - UL | UL 1480 (EJEA) approved |
| RoHS | Approved |