

Avenview MP-1080HDMVL AVSignPro - Digital Signage Player with Live Video Input

ITEM	DESCRIPTION
UNIT	MP-1080HDMVL
UNIT DESCRIPTION	1080p Digital Signage Player with Live Video Input
HDMI STANDARD	HDMI 1.4
SUPPORTED RESOLUTION	480i~1080p (1920x1080)@60Hz
PRIVACY AND SECURITY	Password Protection
CONTROL	OSD, PC Software, RS-232
AUDIO SUPPORT	Supports LPCM 2/5.1/7.1CH, Dolby Digital 2/5.1CH, DTS 2/5.1CH (Bypass), DolbyTrueHD and DTS-HD Master Audio
INPUT PORTS	1x RJ45, 3x USB 2.0, 1x Micro SD Slot 1x HDMI, 1x VGA, 1x Micro USB (avenview use), 1x RS 232
OUTPUT PORTS	1x HDMI, 1x SPDIF (Optical), 1x 3.5mm Audio Out
CONNECTIVITY	Wireless: 802.11 b/g/n, HDMI 1.4(Full-HD 1080p with audio), Ethernet 10/100 BASE-T, 3.5mm analog stereo audio out, S/PDIF out, USB 2.0 x 2, Micro USB for ADB, Optional 3G/4G mobile module via USB
LOCAL STORAGE	16 GB eMMC built-in (approx. 360 minutes of typical 720p video @3 Mbps)
CONTROL	PC Software and OSD
DIMENSIONS (L X W X H)	5.45" x 5.04" x 1.19"
POWER SUPPLY	100-240V, 50-60 Hz, 0.5A Max.12V/1.5A DC
CERTIFICATION	CE/FCC/IC
LED	Power ON LED
WEIGHT	0.74 lbs
ENVIRONMENTAL	
OPERATING TEMPERATURE	32° ~ 104°F (0° to 40°C)
STORAGE TEMPERATURE	-4° ~ 140°F (-20° ~ 60°C)
ESD PROTECTION	Human body model — ±8kV (air-gap discharge) & ±4kV (contact discharge)
RELATIVE HUMIDITY	20~90% RH (no condensation)