

Roland SPD-SX Sampling Percussion Pad

Pads	Built-in Pads: 9 (with LED Indicators) * Two external trigger inputs are provided, allowing you to connect up to four Pads.
Maximum Polyphony	20 voices * Maximum polyphony becomes 16 voices according as an operating state.
Number of Recordable Wave Data	10,000 * Including preload wave data.
Sampling Time (Total time for all wave data)	Approx. 360 min. in stereo (720 min. in mono) * Since the internal memory included with the SPD-SX contains preload data, the available sampling time will be less than the time above.
Data Format	16-bit linear PCM (WAV/AIFF)
Sampling Frequency	44.1 kHz
Kits	100
Kit Chain	8 chains (20 steps per chain)
Effects	Master Effects (21 Types) Equalizer Kit Effect 1 (20 Types) Kit Effect 2 (20 Types)
Display	Graphic LCD 128 x 64 dots
Connectors	PHONES jack (Stereo 1/4-inch phone type) MASTER OUT jacks (L/MONO, R) (1/4-inch phone type) SUB OUT jacks (L/MONO, R) (1/4-inch phone type) AUDIO IN jacks (L/MONO, R) (1/4-inch phone type) (with LINE-MIC GAIN control) TRIG IN jacks (1/2, 3/4) (1/4-inch TRS phone type) FOOT SW jack (1/2) (1/4-inch TRS phone type) MIDI connectors (IN, OUT) DC IN jack COMPUTER connector USB MEMORY connector
Interface	Hi-Speed USB (USB-MIDI, USB-AUDIO, USB Mass Storage Class, USB Flash Drive)
Power Supply	DC 9 V (AC Adaptor)
Current Draw	600 mA
Accessories	CD-ROM (SPD-SX Wave Manager, USB driver, preload wave data) Owner's Manual AC Adaptor
Options (sold separately)	Pads (PD series, PDX series) Cymbals (CY series) Kick Triggers (KD series) Pad Stand (PDS-10) All-Purpose Clamp (APC-33) Acoustic Drum Trigger (RT-30H, RT-30HR, RT-30K) Pedal Switch (DP-2) Footswitch (BOSS FS-5U, BOSS FS-6) Personal Drum Monitor (PM-10, PM-30) USB Flash Memory * Use USB Flash Memory sold by Roland. We cannot guarantee operation if other products are used.
SIZE AND WEIGHT	
Width	364 mm 14-3/8 inches
Depth	331 mm 13-1/16 inches
Height	94 mm 3-3/4 inches
Weight	2.5 kg 5 lbs. 9 oz.