

# Apantac MD-12-4# Cost Effective Dual Output Hybrid (16x2) (12 SDI+4 HDMI) Multiviewer

<b>MODEL</b>	<b>MD-X-X# Cost Effective Dual Output Hybrid (16x2) (HDMI+SDI) Multiviewer</b>		
<b>Inputs</b>	Combinations of HDMI and 3G/HD/SD-SDI	<b>Video Outputs</b>	2 independent DVI/HDMI, SDI outputs
<b>HDMI Connectors</b>	HDMI Type-A Female	<b>Audio Outputs</b>	AES and Analog audio monitor outputs
<b>SDI Connectors</b>	BNC IEC 61169-8 Annex A	<b>Output Resolution</b>	1920 x 1080p 50/60Hz
<b>Total Windows</b>	32+	<b>On-Screen Display</b>	Borders, labels, tally UMD, OMD, IMD, dynamic UMD
<b>HDMI</b>	480P, 720P, 1080i, 1080P 50/60Hz	<b>General Purpose IO</b>	Up to 32 inputs with RJ50 - DB9 connectors
<b>Serial Digital</b>	SMPTE 424M, 292M, 259M	<b>Serial Port</b>	Connector: RJ45, Baud Rate up to 115200 Format, TSL, TSI, AXP
<b>HDMI Audio</b>	4 channels per input	<b>IP</b>	100 Base-Tx, TSL, AXP Connector: RJ45
<b>SDI Audio</b>	SMPTE-272M-A	<b>Electrical</b>	50W, 90-250V 50/60 Hz
<b>Alarms</b>	No audio, audio high/low, no video	<b>EMI/RFI</b>	Complies with FCC Part 15 Class A, CE, EU EMC, C-tick
<b>Power</b>	90-250 AC / 12 DC	<b>Size</b>	1 RU, 25 cm (10")