

Electro-Voice EVIDP6.2W 6.5 inch Pendant Speaker/White (EA)

Rated frequency range	60 Hz - 20 kHz
Sensitivity (SPL 1 W/1 m)	87 dB
Coverage pattern	115° conical
Power handling (@ 8Ω)	75 W (with overload protection)
Rated impedance	8 Ω
Recommended High-Pass frequency	60 Hz
Input configuration	8Ω; 70V/100V
70V/100V power taps	1.8 (70V only)/3.7/7.5/15/30 W
LF transducer	6.5 in (165 mm) high-compliance driver (weatherized cone)
HF transducer	1 in (25 mm) titanium dome
Mounting system	Rear mounted suspension points
Acoustic design	Ported cabinet, two-way design, internally damped, w/passive crossover
Approvals	CE, UL 1480A, CSA 22.2
Cabinet construction	UL94V-0 rated enclosure and baffle
Grille construction	Powder-coated steel
Color	white
Dimensions (depth x diam.)	11.9 in x 12.2 in (301.0 mm x 310.0 mm)
Net weight	11.65 lb (5.28 kg)
Shipping weight	13.85 lb (6.28 kg)
Included accessories	Grille removal tool
Included hardware:	
	Pendant Suspension Cable
Material	Steel wire rope
Working load limit	10 kg (22 lb)
Length	4.57 m (15 ft.)
Approvals	UL2442