

PureLink HCE III-L Rx HDTools 4K HDMI/HDR/IR and RS-232/Bi-directional PoE over HDBaseT Extender (Receiver)

Technical Specifications	
Connector Type/s (Tx)	Inputs: (1) HDMI Type A (1) 3.5mm stereo mini jack (1) USB [firmware] 1) RS-232 Outputs: (1) HDMI Type A (Loop Out) (1) RJ45 (1) 3.5mm stereo mini jack
Connector Type/s (Rx)	Inputs: (1) RJ45 (1) 3.5mm stereo mini 1) USB [firmware] Outputs: (2) HDMI Type A (1) RS-232
Compliance	HDMI 2.0, HDCP 2.2, HDCP 1.4
Video Bandwidth	up to 18 Gbps
Supported Resolutions	4K@60Hz (4:4:4), 1080p, 1080i, 720p(50Hz), 576p, 480p,576i,480i
HDMI Audio	Support DTS-HD, Dolby-HD
Transmission Distance	Ultra HD/4K up to 130ft. (40m), 1080p up to 230 ft. (70m)
Dimensions (WxDxH)	5.5" x 2.6" x 0.8" (139.4mm x 66.8mm x 20mm)
Weight (Tx/Rx)	1.19 lbs. (0.54kg)
Power Supply	DC 24V/1A