

KVM-TEC MVX2-FR Masterline Dual DVI/VGA/USB2.0/Audio Fiber Extender (Receiver)

		MVX2-F Remote/CON
Interfaces	Video:	2 x DVI-D out
	USB 2.0:	4 x USB-A (devices)
	Audio:	1 x 3,5mm jack plug (Line In) 1 x 3,5mm jack plug (Speaker)
	RS232: (optional)	1 x D-Sub connector(male)
Video	Signal type: Resolution (digital): Resolution (analog): (opt.) Color mode:	DVI-D max. 1920x1200 @60Hz max. 1920x1200 @60Hz 24bit
Audio (Optional)	Type: Bandwidth:	
USB	Specification: Type: Rate:	
RS232 (optional)	Type: Rate: Signals:	
Casing	Material: Dimension (W x H x D): Weight:	anodized aluminum 198 x 40 x 103.5 mm (7,79x1,57x4,07") 582g (20,5 oz)
Power supply	Type:	external power supply 12VDC 2A
Power input	Operation:	12W without USB devices
Operation environment	Temperature: Humidity:	0 to +45 ■C (32 to 133 ■F) < 90%, non-condensing
Storage enviroment	Temperature: Humidity:	-25 to 80 ■C (-13 to 176 ■F) < 90%, non-condensing
Cooling		Free air convection
MTBF		82.820 calculated hours approx.10 years
Conformity		CE, FCC
Warranty		2 years (5 years opt)
Delivery including	Devices:	1 x MVX2-F remote (CON)
	Power Supply:	1 x power supply12V 2A (EU-plug)
	Cables:	
	SFP-Module:	1 x SFP Module Multimode up to 500m(1640ft) (Optional with Single-Mode up to 20km/12 mi)
	Mounting:	Quickstart Manual