

Kramer UHDA-IN4-F32 4-Ch 4K60 4x2x0 HDMI Input Card w Selectable Embedded/De-embedded or ARC Analog Audio

PORTS

- 4 HDMI,
- 4 Analog audio on 3.5mm mini jacks

BANDWIDTH PER CHANNEL

- 2.97Gbps per graphics channel

TOTAL BANDWIDTH

- 8.91Gbps data rate

MAXIMUM RANGE

- 10m (32ft) — 4K60 (4:2:0) or 4K30 (4:4:4), 15m (49ft) — 1080p 12 bit (deep color)

3D PASS THROUGH

- Supported

HDMI SUPPORT

- 3D, Deep Color, x.v.Color™, ARC, Dolby® TrueHD, Dolby Digital Plus, DTS–HD®, 7.1 multi–channel audio

POWER CONSUMPTION

- 17W

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- –40° to +70°C (–40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non–condensing

DIMENSIONS

- 19cm x 13cm x 2cm (7.5" x 5.1" x 0.8") W, D, H

PRODUCT WEIGHT

- 0.23kg (0.51lbs) approx

SHIPPING WEIGHT

- 0.37kg (0.82lbs) approx

STANDARD COMPLIANCE

- HDCP 1.4, HDMI 1.4, HDTV compatible

SAFETY REGULATORY COMPLIANCE

- CE

ENVIRONMENTAL REGULATORY COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

PRODUCT DIMENSION

- 22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79") W, D, H

PRODUCT WEIGHT

- 0.3kg (0.7lbs) approx.

SHIPPING DIMENSION

- 25.00cm x 22.50cm x 5.50cm (9.84" x 8.86" x 2.17") W, D, H

SHIPPING WEIGHT

- 0.5kg (1.0lbs) approx.