

Gefen EXT-UHD600A-12-DS 4K Ultra HD 600 MHz 1x2 Scaler with EDID Detective and Audio De-Embedder

- Maximum TMDS Clock: 600 MHz
- Total Signal Bandwidth/Data Rate: 18.2 Gbps
- Video Input Connector: (1) HDMI Type A 19-pin, female, locking
- Video Output Connectors: (2) HDMI Type A 19-pin, female, locking
- Digital Audio Output Connector: (1) TOSLINK® Optical
- Analog L/R Audio Output Connector: (1) 3.5mm mini-stereo jack
- Gefen Syner-G™ port: (1) USB-Mini-B, female
- Power Indicator LED: (1) Blue
- Input (HDMI-Active) Indicator LED: (1) Green
- EDID Selector Switch: (1) Rotary, 8-position
- Power Supply: (1) 5V DC, locking plug, 5.5mm barrel/2.5mm pin
- Power Consumption (Sender and Receiver combined): 4W maximum
- Operating Temperature: +32 to +122 °F (0 to +50 °C)
- Operating Humidity: 5% to 90% RH, non-condensing
- Storage Temperature: -4 to +185 °F (-20 to +85 °C)
- Storage Humidity: 0% to 95% RH, non-condensing
- MTBF: 50000 hours
- Dimensions (W x H x D, Sender/Receiver): 3.7" x 1" x 3.2" (94mm x 25mm x 82mm)
- Net Weight: 0.3 lbs (0.14 kg)
- Shipping Weight: 1.4 lbs (0.63 kg)