

Hall Research HSM-44-BX 4K 4x4 Simultaneous HDMI/HDBaseT Matrix Switch

Input Ports:	4xHDMI IN
Output Ports:	4x HDMI OUT 4x HDBaseT
HDCP:	HDCP 2.2 and HDCP 1.4
HD Resolutions:	480i, 480p, 576i, 576p, 720p: 1080i, 1080p 8, 12 or 16 bits per channel (24, 36 or 48 bits aggregate), 4K30 4:4:4, 4K60 4:2:0
PC Resolutions:	VGA through UXGA
Audio:	4x Coax (S/PDIF digital supports all format listed below) 4x 3.5mm (Analog Stereo, L/R, supports only 2-channel formats) PCM2, PCM5.1, PCM7.1, Dolby5.1, DTS5.1, DD+, D-TrueHD, DTS-HD 16/20/24 bits per sample and up to 96 KHz Sampling Rate
Control:	Front Panel / Telnet/ RS232/ IR
Baud Rate:	115200 bps
Power Supply:	110-240vAC Internal (US/EU standards/ CE/FCC/UL certified)
Power Consumption:	50 W (Max)/0.5 W (Standby)
Housing:	Metal Enclosure
Color:	Black
ESD Protection:	Human body model - ± 12 kV [air-gap discharge] & ± 8 kV
Operating Temp:	32 to 122°F (0 to 50 °C) 10%~90%, non-condensing
Storing Temp:	-40 to +158°F [-40 to +70 °C]
Model Dimensions:	17.30"(440 mm) W x 7.80"(200 mm) D x 1.8"(45 mm) H
Shipping Dimensions:	18.5"(469mm) x 13.6"(345mm) x 5.5"(140mm)
Net Weight:	7.6 lbs. (3450 g)
Shipping Weight:	9.5 lbs. (4310 g)
EMI/EMC:	CE, FCC Class B
MTBF:	90,000 hours