

# WyreStorm SP-0102-H2 1x2 4K HDMI2.0 (18Gbps) Splitter with HDCP 2.2

## Audio and Video

<b>Inputs</b>	1x HDMI 19-pin type A
<b>Outputs</b>	2x HDMI 19-pin type A
<b>Audio Formats</b>	2ch PCM   Up to DTS-X and Dolby Atmos
<b>Max. Video Resolution</b>	1920x1080p @60Hz 12bit (15m/49.2ft)   16bit (15m/49.2ft) 3840x2160p @30Hz 4:4:4 8bit (15m/49.2ft)   @24Hz 4:2:0 HDR 10bit (15m/49.2ft) 4096x2160p @60Hz 8bit 4:2:0 (15m/49.2ft)   @60Hz 8bit 4:4:4 (3m/9.8ft)
<b>Color Depth</b>	1080p: 48bit   4K UHD: 24bit   HDR @24p: 10bit BT.2020
<b>Maximum Pixel Clock</b>	HDMI: 600mHz

## Communication and Control

<b>HDMI</b>	HDMI   HDCP 2.2   Configurable EDID   DVI/D supported with adapter (not included)
-------------	---

## Power

<b>Power Supply</b>	Input: 100~240V AC 50/60Hz   Output: 12V DC 0.5A
<b>Max Power Consumption</b>	3.7W

## Environmental

<b>Operating Temperature</b>	32°F ~ 113°F (0°C ~ 45°C) 10% ~ 90%, non-condensing
<b>Storage Temperature</b>	-4°F to ~ 158°F (-20°C ~ +70°C) 10% ~ 90%, non-condensing
<b>Maximum BTU</b>	13.64 BTU/hr

## Dimensions & Weight

<b>Rack Units/Wall Box</b>	0.34U
<b>Height</b>	N/A   15mm/0.6in
<b>Width</b>	N/A   100mm/3.94in
<b>Depth</b>	N/A   70.2mm/2.77in
<b>Weight</b>	0.2kg/0.44lbs

## Regulatory

<b>Safety and Emission</b>	CE   FCC
----------------------------	----------