

# SWIT M-1051H Triple 5-inch SDI/HDMI Rack LCD Monitor

LCD Performance		
Size	5 inches	
Display area	108x65mm	
Resolution	800x480	
Aspect ratio	16:9 (4:3 adjustable)	
Brightness	350cd/m2	
Contrast	500:1	
Color	16.77 million colors	
Viewing angle	Horizontal: 140°Vertical: 120°	
Input (Each LCD)		
BNC x1	3G/HD/SD-SDI input	
BNC x1	Composite input	
HDMI x1	HDMI input	
Output (Each LCD)		
BNC x1	3G/HD/SD-SDI loop output	
BNC x1	Composite loop output	
HDMI x1	HDMI loop output	
3.5mm x1	SDI and HDMI audio output	
Video Format		
CVBS	NTSC■PAL	
SDI	SMPTE-425M	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080i (60 / 59.94 / 50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
HDMI	480i/ 576i / 480p / 576p	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
General		
Working voltage	DC 6.5V-17V	
Power consumption	≤24W	
Working temperature	0°C■+40°C	
Working humidity	10%■90%	
Storage temperature	-15°C■+60°C	
Storage humidity	10%■90%	
Dimensions	483x130x42mm	
Net weight (main body)	2.1kg	