

SWIT S-4914T/R SDI/HDMI 670m/2200ft Wireless System/Gold-Mount or V-Mount

Model		Transmitter S-4914T	Receiver S-4914R
Input		3G/HD/SD-SDIx1	/
		HDMIx1	
Output		/	3G/HD/SD-SDIx1
			HDMIx1
SDI Format	SMPTE-425M	1080P (60 / 59.94 / 50)	
	SMPTE-274M	1080i (60 / 59.94 / 50)	
		1080p (30 / 29.97 / 25 / 24 / 23.98)	
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)	
	SMPTE-296M	720p (60 / 59.94 / 50)	
	SMPTE-125M	480i (59.94)	
	ITU-R BT.656	576i (50)	
HDMI format		1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
		1080i (60 / 59.94 / 50)	
		720p (60 / 59.94 / 50)	
		480i / 576i	
Wireless frequency		5.1 ~ 5.9GHz	
Radio modules		OFDM 16QAM	
Max Transmission distance		Approx 2200ft (Line of sight)	
Latency		≤1 millisecond	
Power consumption		≤6.5W	≤6.5W
Radio power		Max 21dBm (63mW)	/
Input voltage		DC / Battery:6.5~17V	DC / Battery:6.5~17V
Working environment		Temperature: 0°C ~+40°C	
Dimension		71x120x37 (mm)	130x188x47 (mm)
Net weight(with antenna)		300g	797g