

Gefen GTB-UHD600-HBT 4K Ultra HD HDBaseT Extender (Transmitter/Receiver) Set/POL

- **Maximum TMDS Clock:** 600 MHz
- **Total Signal Bandwidth/Data Rate:** 18.2 Gbps
- **Video Input Connector (Sender):** (1) HDMI Type A 19-pin, female, locking
- **Video Output Connector (Receiver):** (1) HDMI Type A 19-pin, female, locking
- **Link Connector (Sender/Receiver):** (1) RJ-45, shielded
- **RS-232 port (Sender):** (1) 3-pin Phoenix
- **RS-232 port (Receiver):** (1) 3-pin Phoenix
- **IR In/Ext port (Sender/Receiver):** (1) 3.5mm mini-stereo jack
- **IR Extender type:** EXT-RMT-EXTIRN
- **IR Out port (Sender/Receiver):** (1) 3.5mm mini-mono jack
- **Power Indicator LED (Sender/Receiver):** (1) Blue
- **Link Indicator LED (Sender/Receiver):** (1) Green
- **HDMI-Active Indicator LED (Sender/Receiver):** (1) Green
- **Power Supply:** (1) 12V DC, locking, 5.5mm barrel/2.1mm pin
- **Power Consumption (Sender and Receiver combined):** 14W maximum
- **Operating Temperature:** +32 to +113 °F (0 to +45 °C)
- **Operating Humidity:** 5% to 90% RH, non-condensing
- **Storage Temperature:** -4 to +185 °F (-20 to +85 °C)
- **Storage Humidity:** 0% to 95% RH, non-condensing
- **MTBF:** 50000 hours
- **Dimensions (W x H x D, Sender/Receiver):** 4.7" x 1" x 2.9" (119mm x 26mm x 73mm)
- **Net Weight (Sender/Receiver):** 0.3 lbs. (0.14 kg) each
- **Shipping Weight:** 2.1 lbs (0.95 kg)

*Features and specifications are subject to change without notice.