

LTS CMHT1752N Platinum Turret HD-TVI Camera 5MP/3.6mm

| | | |
|--------------------------|-------------------------------|--|
| Camera Series | Platinum Series | |
| Camera Resolution | 5MP | |
| Camera Technology | HD-TVI | |
| Camera Housing | Turret | |
| Featured Product | No | |
| Specifications | CAMERA | |
| | Image Sensor | 1/2.7" CMOS |
| | Signal System | NTSC/PAL |
| | Effective Pixels | 2560(H)*1944(V) |
| | Min. Illumination | 0.01 Lux, 0 Lux with IR |
| | Lens | 3.6mm; FoV: 94° |
| | Shutter Speed | 1/30 (1/25) to 1/50,000 s |
| | Day & Night | ICR |
| | Synchronization | Internal |
| | Video Frame Rate | 2560 x 1944@20fps |
| | HD Video Output | 1 HD-TVI Output |
| | S/N Ratio | More than 62dB |
| | MENU | |
| | AGC | Support |
| | D/N Mode | Color/ BW/ SMART |
| | White Balance | ATW/ MWB |
| | BLC | Support |
| | Function | DNR, Mirror, SMART IR |
| | GENERAL | |
| | Working Temperature /Humidity | -40 °F ~ 140 °F (-40 °C ~ 60 °C) Humidity 90% or less (non-condensing) |
| | Power Supply | DC 12V |
| | Power Consumption | Max. 5W |
| | Weather Proof Ratings | IP67 |
| | IR Range | Up to 131ft (40m) |
| Dimensions | 4.3 "x3.7" (110.0x93.2mm) | |
| Weight | 0.8 lbs (350g) | |