

## Turbosound TLX215L Compact Dual 15 inch Subwoofer for Portable and Fixed Installation Applications

|  |  |
|--|--|
| Frequency response                           | 48 Hz - 150 Hz $\pm$ 3 dB<br>40 Hz - 200 Hz -10 dB |
| Nominal dispersion                           | Half space   |
| Power handling (IEC)                         | 1000 W continuous, 4,000 W peak                    |
| Sensitivity                                  | 101 dB (1 W @ 1 m)                                 |
| Maximum SPL                                  | 131 dB continuous, 137 dB peak                     |
| Impedance                                    | 4 $\Omega$   |
| Components                                   | 2 x 15" (381 mm) LF driver                         |
| Connectors                                   | 2 x Neutrik speakON* NL4                           |
| Wiring                                       | Pins 1+ / 1- input, pins 2+ / 2- link              |
| Dimensions H x W x D                         | 506 x 802 x 751 mm (19.9 x 31.6 x 29.6")           |
| Net Weight                                   | 65.0 kg (143 lbs)                                  |
| Construction                                 | 18 mm (¾") plywood                                 |
| Finish                                       | Semi matt black paint                              |
| Grille                                       | Powder coated perforated steel                     |
| Suspension Hardware                          | Integral   |
| TLX215L-WHB wheel board<br>TLX84-FLB fly bar |  |