

Osprey 95-00473 PCIe Composite/S-Video Capture Card with Stereo Audio (260e)

Description:

- Single channel analog

Format:

- PCIe(x1):
- Slots: x1, x4, x8, or x16
- PCIe 1.1

Video Input:

- Composite
- Component
- S-Video

Video Connector:

- Composite (BNC x 1):
- Y/C (BNC x 2) (BNC to mini-DIN adapter included)
- Component (BNC x 3)

Video Modes:

- NTSC/PAL
- 720 x 480 29.97, 30/i (NTSC)
- 852 x 480, 29.97, 30/i (NTSC Wide Screen)
720 x 576 25/i (PAL)
- Wide Screen Signaling (WSS)

Audio Input:

- Unbalanced stereo (RCA x 2)

Audio Output:

- Unbalanced stereo line (3.5 mm)

Audio Connector:

- Unbalanced stereo (RCA x 2)
- Unbalanced (3.5 mini phono) stereo

Dimensions:

- 5.00" L x 2.71" H (12.70 cm Lx 6.88 cm H)
Low profile/half length

Weight:

- = 65 g

Power Consumption:

- 3.58 W

Operating Temp Range:

- 0° to 40° C

Non-Operating Temp Range:

- -40° to +75° ■

Rel Humidity Operating:

- Between 5 % and 80 % (noncondensing)

Rel Humidity Non-Operating:

- 95 % RH (non-condensing); gradient 30% per hour

Operating Altitude Range:

- 0 to 3,048 meters (10,000 feet)

Non-Operating Altitude Range:

- 0 to 15,240 meters (50,000 feet)

Warranty:

- 1 year limited hardware warranty

Compliance:

- CE, FCC, ROHS, WEEE