

# SECO-LARM EB-P316-60MQ 16 Channel Video/Power/Data Passive Midpoint Combiner

Type	Passive Midpoint
Channels	16
Video Range - CVBS	984' (300m)
Video Range - HD-AHD	720p: 1050' (320m); 1080p: 722' (220m)
Video Range - HD-CVI	720p: 1476' (450m); 1080p: 820' (250m)
Video Range - HD-TVI	720p/1080p: 820' (250m)
Video Format	NTSC, PAL, SECAM
Maximum Input	1.0Vp-p
Frequency Response	DC to 60MHz
CMMR	60dB, 20kHz~60MHz
Wire Category	CAT5e~CAT6
BNC Connection	Nickel-plated
Impedance - Coax	75Ω@1MHz
Impedance - RJ45	100Ω@1MHz
Max. Amperage	1A @ 12VDC/24VAC
Data Range	2,400' (800m)
DC Loop Resistance	29Ω/1,000' (9.5Ω/100m)
Differential Capacitance	19pF/ft max (62pf/m max)
Output Voltage	N/A
Fuse	1.5A max/CH
Input Power	N/A
Input Power Fuse	N/A
Operating Temperature	-14~140°F (-10~60°C)
Operating Humidity	0~95%, non-condensing
Material	Steel
Weight	1.93-lbs (876g)
Dimensions	16-15/16" x 1-3/4" x 15/16" (430mm x 44mm x 33mm)