

SECO-LARM MVE-AH030AQ HDMI Extender (Transmitter/Receiver) Kit over Single CAT5e/6 UTP cable with Loop/Audio out

Input Video Signal	3.3V
Input DDC Signal	5Vp-p (TTL)
Deep Color	24bit
Video Format Supported	High-speed HDMI®, HDCP 1.2
Audio Formats Supported	LPCM, Dolby-AC3, DTS7.1, DSD
Output Video	HDMI
Resolutions Supported	1080p/1080i/720p/576p/576i/480p/480i
Range	Cat6- Up to 196' (60m), Cat5e- Up to 98' (30m)
Video Amplifier Bandwidth	1.65Gbps
Maximum Input Cable Length	24AWG (15m), 26AWG (10m), 28AWG (5m)
Maximum Output Cable Length	24AWG (15m), 26AWG (10m), 28AWG (5m)
Video Input Connector	HDMI Type A 19-pin female
Video Output Connector	HDMI Type A 19-pin female
Operating Voltage	5VDC
Power Supply	1A@5VDC (2 adapters) (2.1mm plug)
ESD Protection (Human Body Model)	+8kV (air-gap discharge), +4kV (contact discharge)
Cat5e/6 Wiring Standard	T-568B
Current Draw	Transmitter- 550mA@5VDC, Receiver- 450mA@5VDC
Operating Temperature	32°~104° F (0°~40° C)
Operating Humidity	20% to 90% RH (no condensation)
Dimensions	3-15/16" x 2-9/16" x 1" (100 x 65 x 26 mm)
Weight	7.2-oz (205g) (each)
Maximum Single Link Range	1080p