

Electric Door Strike

SD-994C For wood doors, 12VDC, UL Listed

SD-994C24 For wood doors, 24VDC, UL Listed

The **SECO-LARM®** Electric Door Strike can be used to convert cylindrical lock sets into an electronic access-controlled locking system. Combine with an optional **SECO-LARM®** digital keypad for keyless high security.



Features:

- Field-selectable for fail-safe or fail-secure operation
- Can be used with virtually any cylindrical door locking system
- Can use with an optional digital keypad
- Suitable for office-type applications
- Reversible non-handed design fits either right-hand or left-handed doors
- Shallow design for use with most wood doors
- Powered by a solenoid, not a buzzer coil
- Jaw strength – 2,000-lbs. (908kg)
- Stainless-steel keeper for strength and long life
- Non-polarized connection
- Tested to 1 million cycles
- Optional lip-extension brackets available:
 - **SD-995C-LE25** – 1" Extension
 - **SD-995C-LE50** – 2" Extension

Trim Plate Included

Fail-Safe Fail-Secure

Non-Polarized Connection

2000-lbs. Jaw Strength



Trim plate (included)



Extension SD-995C-LE25 shown

Also Available from SECO-LARM®:



**SD-995C
SD-995C24**
Electric Door Strike
for Metal Doors



SD-996C-NUQ
Universal Door Strike

Specifications:

Model #	SD-994C	SD-994C24
Operating voltage	12VDC	24VDC
Current draw	250mA	150mA
Operating temperature	14°~113° F (-10°~45° C)	
Static strength	2,000-lbs. (908kg)	
Dimensions	7 ¹⁵ / ₁₆ "x1 ⁷ / ₁₆ "x1 ¹ / ₄ " (208x36x32 mm)	

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA, 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright © 2016 SECO-LARM U.S.A., Inc. All rights reserved.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.
SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®