

Patton CL1101/PAFA/BNC/EUI-2PK CopperLink PoE Extender Kit/BNC/Line Powered

Line Interfaces (Data)	1 x RJ45 (Optional: Terminal Block, Coax) Supports 1-4 pairs
Ethernet Interfaces	1 x RJ45 Auto-Sensing 10/100Base-TX with full or half-duplex operation
LEDs	Power, Line, (10 or 100 operation), Eth, and PoE
Protocol	Transparent to high layer protocol Supports 802.1Q VLAN tagged frames Transparent to IP video schemes Fully transparent to compression schemes such as WMV, MPEG-4, and MJPEG
Power Injection (PSE only)	DC voltage on Ethernet port 54 VDC
Power Consumption	1.5 W
Power Supply	External AC Adapter 100–240 VAC to 54 VDC Input: 30–57 VDC (Recommended 54 VDC)
MTBF	83,043 hours
Environment	Temperature: 0 to 50°C (standard) Humidity: 10 to 95% (non-condensing)
Physical	4.13 W x 1.5H x 3.15 D in. (105 W x 38.1 H x 95.3 D mm) 0.78 oz (22 g)
Compliance	FCC Part 15A, Class B CE Mark EMC Directive 89/336/EEC LVD Directive 73/23/EEC