

PureLink HOF 2.0 Rx HDTTools 1 LC Fiber to HDMI 2.0/IR/RS-232 to 1 Fiber Extender (Receiver)

This listing is for HOF 2.0 Rx only. Use description below as a general reference.

The **HOF 2.0 Tx/Rx** offers a powerful solution for long-distance distribution of 4K/60 video, audio, and control signals over fiber. Ultra HD/4K, HDMI 2.0 (18G), embedded audio, RS-232, and bi-directional IR are all supported over distances up to 3,300 ft. using PureLink's TOTALWIRE LC-terminated fiber optic cables. The pure fiber connection provides protection from electromagnetic interference (EMI), delivering lossless transport for optimal signal quality.

Key Features

- 4K@60Hz (4:4:4) / 18Gbps / HDCP 2.2
- Extends up to 3300 ft. (1000 m.) over 1 LC single-mode fiber
- Dolby® Atmos, DTS-HD Master Audio, LPCM 2/5.1/7.1
- Bi-directional IR, RS-232
- Real-time Auto-EDID management
- Auto signal correction and enhancement
- Immune to EMI
- 1 LC SFP Modules
- Locking power supplies

Features	Model No.	
	HOF 2.0	
Distance (ft)	3300	
HDMI Version	2.0	
HDCP Version	2.2	
Ultra HD/4K (@50/60Hz, 4:4:4)		
Full HD (1080p)		
Bandwidth (Gbps)	18	
Rack Mounting Option		