

AVPro Edge AC-DAC-COTO Digital to Analog Audio Converter

- **Input Ports**
 - 1xTOSLINK (S/PDIF Audio)
 - 1xRCA (S/PDIF Audio)
- **Output Ports**
 - 2xRCA (Stereo Audio)
- **Input Audio Format**
 - LPCM 2.0
- **Output Audio Format**
 - Analog 2.0
- **Input Sampling Rates**
 - 32kHz, 44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz & 192kHz
- **Output Level**
 - 2Vrms
- **Output Impedance**
 - 600Ω
- **Power Supply**
 - 5V/1.2A DC (US/EU standards, CE/FCC/UL certified)
- **ESD Protection**
 - Human Body Model:
 - ±12kV (Air Discharge)
 - ±8kV (Contact Discharge)
- **Weight**
 - 30g
- **Chassis Material**
 - Plastic
- **Silkscreen Color**
 - White
- **Operating Temperature**
 - 0°C - 40°C / 32°F - 104°F
- **Storage Temperature**
 - 20°C - 60°C / -4°F - 140°F
- **Relative Humidity**
 - 20 - 90% RH (Non-condensing)
- **Power Consumption**
 - 0.74W