

Electro-Voice EKX15PUS 1500 Watt Powered 15 inch Two Way Loudspeaker/48Hz-20kHz

Frequency Range (-10 dB)	48 Hz - 20 kHz (Full space measurement using the music DSP preset)
Weight Net	24.4kg (53.79 lbs)
Depth	429mm (16.89")
Width	432mm (17.01")
Height	685mm (26.97")
Connector Type	(1) Stereo RCA input, (2) XLR/TRS combo jack, and (1) XLR link output
Coverage (Nominal -6 dB) H	90°
Coverage (Nominal -6 dB) V	60°
Crossover Frequency	1.7 kHz
Enclosure Material	15 mm, plywood with EVCoat
Family	EKX
Frequency Response (-3 dB)	55 Hz - 18 kHz (Full space measurement using the music DSP preset)
Grille	18 AWG steel with powdercoat
HF Transducer	DH-1M 1-inch titanium compression driver
LF Transducer	EVS-15M 381 mm (15 in)
Max. SPL/1m (calc)	134dB
Maximum SPL	134dB (Maximum SPL is measured at 1 m using broadband pink noise at maximum output)
Power Consumption	1.8 A (Current rating is 1/8 power)
Power Rating	1500W
Powered or Passive	Powered
Shipping Weight	29.5kg (65.04 lbs)
Speaker Type	Full-Range, two-way
Suspension	(8) M10 threaded mounting points
Woofers Size	15inch