

# Adder AV4PRO-VGA-TRIPLE-US VGA (Triple Video) USB 4 port KVM Switch with USB True Emulation

<b>Mechanical</b>	
Height	100 mm. (10 cm.)
Width	260 mm. (26 cm.)
Depth	150 mm. (15 cm.)
Physical Design	2.5U high metal case
<b>Hardware Compatibility</b>	All computers with USB interfaces
<b>Software Compatibility</b>	Operates with all known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, all Sun OS, all Mac OS, NetWare etc.
<b>Computer connections at switch</b>	USB 2.0 type B, Hi Res VGA (up to 4 connections) 3.5mm stereo jack
<b>Local KVM Console Connection Video</b>	
Video	VGA (Triple x 3)
Keyboard/Mouse	2 x USB type A
Switched USB	2 x USB 2.0 type A Supports USB 2.0 devices in low, full and high speed models.
USB True Emulation	Emulates keyboard and mouse on each port. Low speed HID USB 2.0 devices supported
Audio	3.5mm stereo jack
Other Connections	Options (flash upgrade, sync with other AV4PRO-VGA-TRIPLE and RS232 triggered power switches): Modular 10P10C
<b>Power</b>	2.5mm DC jack (power adapter included), 100-24-VAC 50/60Hz input to power adapter, 5VDC 2A output from power adapter
<b>Operating Temperature</b>	0 degC to 40 degC / 32 degF to 104 degF
<b>Approvals</b>	CE, FCC