

LTS LTN8704Q-P4 4-Ch Platinum Professional Level NVR/Support Live View/Recording/Playback up to 4K

Video/Audio Input	
IP Video Input	4CH
Two Way Audio Input	1- ch, RCA (2.0 Vp- p, 1kΩ)
Incoming Bandwidth	40Mbps
Outgoing Bandwidth	80Mbps
Video/Audio Output	
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
HDMI Output	4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60 Hz, 1280 × 720/60Hz, 1024 × 768/ 60Hz
VGA Output	1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Video Output	1CH, RCA (Linear, 1kΩ)
Decoding	H.265/H.265+/H.264/H.264 Zip+/MPEG4
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	4CH
Capability	1-ch @ 8 MP / 4-ch @ 1 080p
Hard Disk	
SATA	1 SATA interfaces for 1 HDDs
Capacity	Up to 6TB capacity for each disk
External Interface	
Network Interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface
Network Protocols	TCP/IP, DHCP, PT CLOUD, DNS, DDNS, NTP, IP Portal, SMTP, NFS, iSCSI, UPnP™ , HTTPS
USB Port	2 × USB2.0
General	
Power Supply	48V DC
Consumption	≤ 10W (without enabling PoE)
Working Temperature	14°F - 131°F(-10 °C ~ +55 °C)
Working Humidity	10% - 90%
Chassis	1U Casing
Dimension	315 ×240× 48mm (12.4×9.4 × 1.9 inch)
Weight	≤ 1 kg (2.2 lb)