

# Kramer 6410N Digital Audio to Balanced Stereo Audio Format Converter

|                                 |  |
|---------------------------------|--|
| <b>INPUTS:</b>                  | 4 digital audio inputs: AES-3id on a terminal block connector; AES/EBU on a BNC connector; S/PDIF on an RCA connector; TOSLINK® optical connector. |
| <b>OUTPUTS:</b>                 | 2 analog outputs: balanced line out on detachable terminal blocks; 3.5mm headphone jack.   |
| <b>SAMPLE RATE CONVERSION:</b>  | 32kHz, 44.1kHz, 48kHz, 96kHz.  |
| <b>CONVERSION GAIN:</b>         | +12dB, +16dB, +20dB, +24dB.  |
| <b>BANDWIDTH (+4dBu/-3dBu):</b> | 20Hz to 22kHz.   |
| <b>MAX. OUTPUT LEVEL:</b>       | 11.2Vpp @ 1kHz.  |
| <b>S/N RATIO:</b>               | 88dB.  |
| <b>AUDIO THD + NOISE:</b>       | -92dB.   |
| <b>AUDIO 2nd HARMONIC:</b>      | 0.003%.  |
| <b>CONTROLS:</b>                | Input selector buttons, 8 gain switches, headphones level rotary control knob, 2 LEDs: ON and LINK.  |
| <b>POWER SOURCE:</b>            | 12V DC, 1.25A.   |
| <b>DIMENSIONS:</b>              | 12cm x 6.95cm x 2.44cm (4.72" x 2.74" x 0.96") W, D, H.  |
| <b>WEIGHT:</b>                  | 0.3kg (0.66lbs) approx.  |
| <b>ACCESSORIES:</b>             | Power supply, mounting bracket.  |
| <b>OPTIONS:</b>                 | RK-3T 19" rack adapter.  |