

Aten CE820R USB HDMI 4K/100 HDBaseT 2.0 KVM Extender (Remote Unit)

| | |
|------------------------|--|
| Connectors | |
| Console Ports | 1 x HDMI Female (Black) 3 x USB Type A Female 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink) 1 x RJ-45 Female (Black) |
| KVM Ports | N/A |
| RS-232 | 1 x DB-9 Male (Black) |
| Power | 1 x DC Jack with locking |
| Unit To Unit | 1 x RJ-45 Female (Black) |
| LEDs | |
| Power | 1 (Green) |
| Link | 1 (Orange) |
| Video Output | 1 (Orange) |
| Switches | |
| Long Reach Mode Switch | 1 x Slide Switch |
| Firmware Upgrade | 1 x Slide Switch |
| Pushbuttons | |
| Wakeup button | 1 x Push button |
| Video | Up to 4K@90m (Cat 5e) / 100m (Cat 6/6a/ATEN 2L-2910 Cat6) 1080P@100m (Cat 5e/6/6a) *4K supported: 4096 x 2160 / 3840 x 2160 @ 60Hz (4:2:0); 4096 x 2160 / 3840 x 2160 @ 30Hz (4:4:4) |
| Power Consumption | DC5V:5.37W:40BTU |
| Environmental | |
| Operating Temperature | 0–40°C |
| Storage Temperature | -20–60°C |
| Humidity | 0–80% RH, Non-condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 0.65 kg (1.43 lb) |
| Dimensions (L x W x H) | 18.20 x 12.19 x 2.87 cm (7.17 x 4.8 x 1.13 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |