

Electro-Voice ETX35PUS 15 inch Powered Active 3Way Loudspeaker/2000W/38Hz-20kHz

Weight Net	41.7kg (91.93 lbs)
Depth	426mm (16.77")
Width	469mm (18.46")
Height	1023mm (40.28")
Connector Type	(2) XLR/TRS combo jack and (1) XLR link output
Coverage (Nominal -6 dB) H	60°
Coverage (Nominal -6 dB) V	40°
Crossover Frequency	700 Hz, 2900Hz
Enclosure Material	18-mm, 13-ply birch plywood with EVCoat
Family	ETX
Frequency Range (-10 dB)	38 Hz – 20 kHz
Frequency Response (-3 dB)	48 Hz – 20 kHz
Grille	16AWG steel with powdercoat
HF Transducer	DH3-B 1.25-in titanium compression driver
LF Transducer	SMX2151 380 mm (15 in)
Max. SPL/1m (calc)	136dB
Maximum SPL	136 peakdB
MF Transducer	EVS-6C 6.5-in midbass driver
Power Consumption	100 – 240 V~, 50 – 60 Hz, 1.6 – 0.8 A
Power Rating	2000W
Powered or Passive	Powered
Shipping Weight	46.8kg (103.18 lbs)
Speaker Type	Full-Range, three-way, powered speakers
Suspension	(8) M10 suspension points
Woofers Size	15inch