

Kramer DK82PU-N HighSecLabs Dual Head 8-Port 4K30 UHD DisplayPort KVM Switch with sUSB

CONSOLE PORTS

- 2 DisplayPort 1.2 connector
- 2 USB-A connectors for keyboard and mouse
- 3 USB-A 3.0 connectors for USB devices
- 1 3.5mm mini jack for unbalanced stereo audio
- 1 RJ-45 connector for control (RDC)

COMPUTER PORTS

- 16 DisplayPort 1.2 connectors
- 8 USB-B connectors for keyboard and mouse
- 8 USB-B 3.0 connectors for USB devices
- 8 3.5mm mini jacks for unbalanced stereo audio

MAX RESOLUTION

- 4K30 UHD (3840X2160) @30Hz

POWER CONSUMPTION

- 35W max

AC INPUT

- 100 to 240V AC

POWER TYPE

- External

OPERATING TEMPERATURE

- 32° to 104°F (0° to 40°C)

STORAGE TEMPERATURE

- -4° to 140°F (-20° to 60°C)

HUMIDITY

- 0-80% RH, non-condensing

SUPPORTED OS

- Windows, Linux, Mac

PRODUCT CERTIFICATION

- CE, RCM, FCC class B, VCCI, TUV US, TUV Canada

PRODUCT LIFE-CYCLE

- 10 years