

Altinex DA1907LX 1x2 VGA Distribution Amplifier

General	Electrical
Input	Input Video Signal
Input Connector: (1) 15-pin HD female	Analog Signal Level: 1.5V p-p max.
Outputs	Impedance: 75ohms
Outputs 1 & 2: (2) 15-pin HD female	Coupling: DC
Power	Input Sync Signal
DC Power: (1) 2.5mm jack	Horizontal/Vertical or Composite: TTL (+/-)
Compatibility	Sync on Green: -0.3V
Signal Types: RGB, RGsB, RGBS, RGBHV, YPbPr, MAC, SUN, SGI	Impedance: 10kohms
Video Signal Resolution: VGA-UXGA; 480p-1080i	Output Video Signal s
	Gain: 0dB +/-0.5dB
	Impedance: 75ohms
	Coupling: DC
	Output Sync Signal s
	Horizontal/Vertical or Composite: TTL (+/-)
	Sync on Green: -0.3V
	Impedance: 10kohms
	Power Consumption
	External Adapter: 9VDC, 280mA (2.5W max.)
Mechanical	Accessories
Width: 4.50in (114mm)	Included
Height: 3.00in (76mm)	1xPower Adapter, 1.1A
Depth: 1.00in (25mm)	1x3ft (1m) Video cable (15pin HD M-M)
Weight: 0.5lb (0.2kg)	Optional
Shipping Weight: 1.0lb (0.5kg)	MB1001 : "L" Shaped Mini-Brackets
Material: 0.1in Aluminum	
Finish: Gray	
Top Panel: Lexan	
T Operating: 10C to 35C	
T Maximum: 45C	
Humidity: 90% non-condensing	
MTBF (calc.): 40,000hrs	