

Kramer VP-211K-b 2x1 VGA Video and Stereo Audio Standby Switcher

INPUTS:	2 computer graphics video on 15-pin HD connectors; 2 unbalanced stereo audio on 3.5mm mini jacks.
OUTPUTS:	1 computer graphics video on a 15-pin HD connector; 1 computer graphics video looping on a 15-pin HD connector; 1 unbalanced stereo audio on a 3.5mm mini jack.
MAX. OUTPUT LEVEL:	Video: 1.6Vpp; Audio: >10.5Vpp.
BANDWIDTH (-3dB):	Video: 300MHz; Audio: >100kHz.
DIFF. GAIN:	0.03%.
DIFF. PHASE:	0.03Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	Video: 71dB; Audio: 71dB weighted.
CROSSTALK:	Video: -59dB @5MHz; Audio: <-66dB @1kHz.
CONTROLS:	Contact closure remote control, input default selection switch.
COUPLING:	DC.
AUDIO THD + NOISE:	<0.032%.
AUDIO 2nd HARMONIC:	<0.004%.
POWER SOURCE:	5V DC 200mA.
DIMENSIONS:	12.1cm x 7.18cm x 2.42cm (4.76" x 2.83" x 0.95") W, D, H.
WEIGHT:	0.3kg (0.66lbs) approx.
ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.