

Atlona AT-HDDA-4 1 by 4 HDMI Distribution Amplifier

Video Resolutions

- **Video** 480i@60Hz, 480p@59.94/60Hz, 576i@50Hz, 576p@50Hz, 720p@50/59.94/60Hz, 1080i@50/59.94/60Hz, 1080p@23.98/24/25/29.97/30/50/59.94/60Hz, 3840x2160@24/25/30/60Hz (UHD), 4096x2160@24/25/30/60Hz
- **VESA** 640x480, 800x600, 1024x768, 1280x768, 1280x800, 1280x1024, 1366x768, 1440x900, 1400x1050, 1600x1200, 1600x900, 1680x1050, 1920x1200
- **Colorspace** YCbCr, RGB
- **Chroma Subsampling** 4:4:4, 4:2:2, 4:2:0 (UHD only)
- **Color depth** 8-bit, 10-bit, 12-bit

Audio

- **Formats** PCM 2Ch, LPCM 5.1, LPCM 7.1, Dolby Digital, DTS 5.1,
- **Dolby Digital** Plus, Dolby TrueHD, DTS-HD Master Audio
- **Sample Rate** 32kHz, 44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz

Distance

- **HDMI IN** up to 15 meters (@1080p 8-bit) up to 50 feet
- **HDMI OUT** up to 15 meters (@1080p 12-bit) up to 50 feet
- **4K** up to 5 meters up to 15 feet

Signal

- **Bandwidth** 10.2 Gbps
- **CEC** No
- **HDCP** Compliant

Temperature

- **Operating** 0°C to 40°C 32°F to 104°F
- **Storage** -20°C to 60°C -4°F to 140°F
- **Humidity** 20 to 90% non-condensing

Power

- **Consumption** 5W
- **Supply Input:** AC100~240V 50/60Hz / **Output:** DC 5V/3A

Dimension

- **H x W x D** 44 x 433.8 x 255 (mm) 1.73 x 17.08 x 10.04 (inch)
- **w/feet** 55.15 x 433.8 x 255 (mm) 2.17 x 17.08 x 10.04 (inch)
- **Rack Unit** 1

Weight

- **Device** 2.61 kg 5.75 lbs
- **Shipping** 4.22 kg 9.3 lbs

Certification

- **Power Supply** CE, FCC, RoHS, cULus