

# Altinex UT260-104 HDMI to HDBASET Under Table Extender (Receiver)

<b>Input Connectors</b>	
HDMI Over HDBT	RJ-45 F (1)
Power	DC Jack 2.5 mm F (1)
<b>Output Connectors</b>	
Digital Video + Audio	HDMI F. Type A (1)
<b>Control</b>	
RS232/Input Select	Term. Blk. 3 position (1)
IR Output (to emitter)	3.5 mm F (1)
IR Input (from sensor)	3.5 mm F (1)
<b>Compatibility</b>	
Digital Signal types	HDMI 1.4,3D, 4k 30Hz DP 1.2
Signal resolution	Up to 4k x 2k 30 Hz
VGA	VESA up to 1920x1080
<b>Accessories Included</b>	
Power Supply	24V/1A Power Adapter (1 )
Mounting Brackets	Right Angle (2)
Terminal Blocks	3 position, 3.5 mm (1)
<b>Optional Accessories</b>	
IR Emitter	AC301-114
IR Receiver	AC301-116
<b>Mechanical</b>	
Material	Steel
Color	Black
Height	0.98 in. (25 mm)
Width	2.95 in. (75 mm)
Length	4.37 in. (111 mm)
Weight	1.3 lb. (0.6 kg)
T° Operating	10°C-40°C
Humidity	60% RH non-condensing
MTBF (calc.)	38,000 hrs.
<b>Electrical</b>	
Video Input Signals	
Digital Video + Audio on HDBT	Altinex Standard
Output Signals	
Digital Video + Audio	HDMI Standard
Power	
+24VDC	500 mA, 24 W