

Panamax MFP-300 Versatile 2 Outlet Surge Protector/Power Filter with Cable/Sat Signal Protection

General

- Family: Power Conditioners
- Line Voltage: 120 (Volts)
- BlueBOLT Enabled: No
- Number of Outlets: 2
- Outlet Descriptions: Both outlets filtered and surge protected
- Compliance: UL 1449 3rd Edition, 3,000A
- USB Charging: N/A
- Low Voltage Trigger: N/A
- AC Power Cord: 6 ft. captive cord
- Dimensions: 3.75" W x 8.5" L x 1.6 in H
- Weight: 2 lbs

AC Protection

- AC Protection Technology: Protect or Disconnect
L-N, L-G, N-G Protection Modes
Thermal Fusing
- Automatic Voltage Shutoff: No
- Undervoltage Shutoff: N/A
- Over-Voltage Shutoff: N/A
- Maximum Current Rating: 12 (Amps)
- Initial Clamping Level: 200V Peak

Filtration

- Filtration Technology: RFI/EMI Filtration
- Filtration Rating: 43 dB @ 100kHz - 1MHz

Signal Line Protection

- Signal Line Protection: 1 Cable/Satellite

Shipping Info

- Length: 11.5 (Inches)
- Width: 9.2 (Inches)
- Height: 2.1 (Inches)
- Weight: 2.5 (Lbs)
- Unit of Measure: Each
- UPC: 050616008242
- Master Pack Qty: 6

Other Specifications

- Voltage Protection Rating (UL 1449 3rd Edition, 3,000A): 330V
- UL991 Electronic Safety Circuit: Yes
- Single Pulse Energy Dissipation: 1675 Joules
- Response Time: < 1ns
- Peak Impulse Current: 48,000 Amps

Universal Coaxial Protection

- Shielded: Yes
- Insertion Loss: < 0.5 dB
- Frequency Range: 0MHz - 2.2 GHz
- Connections: Female "F", Gold Plated
- Clamping Level: 75V
- Bidirectional: Yes