

# Gefen EXT-DPKA-LANS-KIT 4K DisplayPort KVM over IP Extender (Transmitter/Receiver) Kit

- Video Input connector (Sender): (1) DP-20-pin, female
- Video Output connector (Receiver): (1) DP-20-pin, female
- Line Input (Sender): (1) 3.5mm mini-stereo jack
- Line Output (Sender): (1) 3.5mm mini-stereo jack
- Mic Input (Receiver): (1) 3.5mm mini-stereo jack
- Headphones/Line Output (Receiver): (1) 3.5mm mini-stereo jack
- Optical Digital Audio Output (Receiver): (1) TOSLINK®
- USB Host Interface port (Sender): (1) USB Type B, female
- USB Device ports (Receiver): (2) USB 2.0 Type A, female (2) USB 1.1 Type A, female
- RS-232 port (Sender): (1) DB-9, female
- RS-232 port (Receiver): (1) DB-9, male
- IR Sensor (Receiver): (1) Located on front panel
- IR In/Ext (Sender/Receiver): (1) 3.5mm mini-stereo jack
- IR Out (Sender/Receiver): (1) 3.5mm mini-mono jack
- IR Extender type: EXT-RMT-EXTIRN
- Ethernet port (Sender): (1) RJ-45, shielded, PoE
- Ethernet ports (Receiver): (2) RJ-45, shielded, one with PoE
- Channel Up/USB-Request button (Receiver): (1) tact-type
- Channel Down button (Receiver): (1) tact-type
- Mode button (Sender): (1) tact-type, recessed
- Reset button (Sender/Receiver): (1) tact-type, recessed
- Program button (Sender/Receiver): (1) tact-type, recessed
- Program Select switch (Sender/Receiver): (1) slide-type, recessed
- Link Indicator (Sender/Receiver): (1) LED, green
- Power Indicator (Sender/Receiver): (1) LED, blue
- Power Supply jack (Sender/Receiver): 5V DC, 2.5mm pin and 5.5mm barrel, locking
- Power Requirement (Sender/Receiver): 5V DC, or PoE (802.3af standard)
- Power Consumption: Sender: 6W, Receiver: 26W
- Operating Temperature (Sender/Receiver): +32 to +122°F (0 to +50°C)
- Operating Humidity (Sender/Receiver): 5% to 90% RH, non-condensing
- Storage Temperature (Sender/Receiver): -4 to +185°F (-20 to +85°C)
- Storage Humidity (Sender/Receiver): 0% to 95% RH, non-condensing
- MTBF: Sender: 50000 hours, Receiver: 50000 hours
- Dimensions (W x H x D, without connectors or feet): Sender: 8.4" x 1.7" x 5.9" (214mm x 43mm x 150mm) Receiver: 8.4" x 1.0" x 5.9" (214mm x 25mm x 150mm)
- Unit Weight: Sender: 2.2 lbs. (1 kg), Receiver: 2 lbs. (0.9 kg)
- Shipping Weight: Sender: 4.2 lbs. (1.9 kg), Receiver: 4.2 lbs. (1.9 kg)