

Key Digital KD-MLV4x2Pro 4x2 4K POH/HDBaseT/HDMI/VGA Multi-View Seamless Presentation Matrix Switcher

- **Inputs:** 4 HDMI connector, Type A, 19 pin female; 2 HD analog video 15-pin female, 2 analog audio connector, 3.5mm stereo female
- **Outputs (each):** 1 HDMI connector, Type A, 19 pin female; 1 HDBaseT RJ45 female; 1 digital coaxial audio on RCA connector; 1 L/R Balanced/ Unbalanced on 6-pin Phoenix connector
- **TMDS Bandwidth:** 9 Gb/s total
- **Deep Color Support:** Supports digital video formats in Deep Color Mode up to 8 bits/color with all HDMI and HDCP technologies
- **Link:** Single Link
- **DDC Signal (Data):** Input DDC signal – 5 Volts p-p (TTL)
- **HDMI Video/Audio Signal:** 1.2 Volts p-p
- **DDC Communication:** EDID And HDCP buffering between source and display
- **Wired IR:** Modulated IR signal input, 0-5V TTL or -10 to + 10V
- **Power:** External power supply; 12V/5A
- **Regulation:** CE, RoHS, WEEE
- **Enclosure:** Black metal
- **Rack Mount:** 1U, full rack-width (rack ears included)
- **Product:** 17.25" x 8.875" x 1.75"; Weight: 6.5 lbs
- **Packaging:** 18.5" x 13" x 3.5"; Weight: 8.8 lbs