

# Atlona AT-PROHD1632M-SR BUNDLE PACKAGE 16x32:2 PRO HDMI Matrix Switch with CAT5/6 and Local HDMI Outputs

Atlona BUNDLE PACKAGE 16x32:2 HDMI Matrix Switch with CAT5/6 and Local HDMI Outputs with 3D Support. (32 x HDMI Receivers are included)

**Model: AT-PROHD1632M-SR**

The Atlona AT-PROHD1632M-SR is a True 8x16:2 HDMI matrix switch. The PROHD1632M unit features eight HDMI 1.3 inputs, and 32 independently switchable HDMI + Twisted Pair outputs to feed 32 separate displays simultaneously. Each output features 1 x HDMI and 2 x Twisted Pair connections where both are active at the same time. Twisted Pair outputs are used to connect to the 32 x included receiver modules.

The AT-PROHD1632M-SR has the ability of equalization, amplification and re-clocking the signal to ensure HDMI accurate signal transmission through long cables without quality loss. The transmission distance of Twisted Pair (CAT5/6) outputs can reach up to 165ft @ 1080P. Distance can be extended for additional 165ft with an optional Atlona repeater unit AT-PROHD-RP. It is recommended to use CAT6 (568B terminated) wire to achieve longer lengths.

**The AT-PROHD1632M-SR bundle package includes:**

- 2 x AT-PROHD1616M-SR (HDMI matrix switcher)
- 16 x AT-HD-V12 (1 x 2 distribution amplifier)
- 48 x 2m HDMI cables

**The Atlona 16x32:2 Matrix Bundle Package can ONLY be controlled through RS232.** IR and TCP/IP features are not functional in this package.

**Features:**

- **3D Capable**
- Supporting the latest (HDMI1.3) 36 bit deep color standard, it can be connected even to the latest Blu-ray players, set top boxes, AV receivers or Apple TV.
- HDCP 1.1 and DVI1.0 compliant.
- **Supports high resolution up to 1920x1200 or 1080p** over local HDMI or included Twister Pair receiver modules.
- The 32 outputs are capable of displaying the same or different sources simultaneously. Each output includes one HDMI A type connector and a set of dual RJ45 connectors as the second mirrored HDMI output. The two outputs work simultaneously.
- Supports all latest HDMI digital audio format pass through including Dolby TrueHD and DTS-HD Master.
- EDID management function stores 100 most common EDID recordings with ability of programming new EDID recording by the user.
- Reclocking for both inputs and outputs allows long HDMI Cables cables to be used.
- Control options: Front panel buttons and RS232.
- RS232 commands are provided.
- **Silicon Image Chip-Sets allow %99.99 device compatibility. Silicon Image was a creator of the HDMI standard.**
- Rack Mountable (comes with rack ears)
- Control4, RTI, Crestron, AMX compatible

**Technical Specifications:**

- Video Bandwidth: 6.75Gbps
- Max Resolution : 1080p/1920 x 1200
- HDTV Formats Supported: 1080P/1080i/720P/576P/480P/576i/480i
- PC Formats Supported: VGA, SVGA, XGA, SXGA, UXGA, WXGA, WSXGA, WUXGA
- Supports all latest HDMI digital audio format pass through including Dolby TrueHD and DTS-HD Master
- Maximum HDMI Cable Input/Output Distance 50ft
- Maximum twisted pair output Distance 165ft @1080p (optional repeater is available to add an additional 165ft (Model: AT-PROHD-RP)
- Twister Pair Type: CAT5/6/7 (568B termination)
- Power Consumption: Each Main Unit: 60 watts (Max); Receiver Unit 100 milliwatts (Max)
- Dimensions (Inch): Each Main Unit:17.32W X 13.78 X 15.35D Receiver:1.8W X 0.8H X 3.3D
- Dimensions (mm): Each Main Unit: 440W X 350H X 389D Receiver: 46W X 20H X 84D
- Net Weight: Each Main Unit: 44.1 LB; Receiver Unit: 0.6LB
- Net Weight: Each Main Unit: 20kg; Receiver Unit: 0.27kg
- U Dimensions: 6U

**Bundle Package Includes:**

*Main Unit:*

- 2 x AT-PROHD1616M-SR

- 32 x IR emitter cables (marked IR TX) **NOT UTILIZED IN THIS PACKAGE**
- 2x IR receiver cables (marked IR RX) **NOT UTILIZED IN THIS PACKAGE**
- 2 x USB to RS232 cable
- 2 x 12VDC Universal Power Supply. (UL Listed)
- 2 x pair rack mounting ears.
- 2 x IR remote.

*Receiver Modules:*

- **32 x Receiver Units AT-PROHD1616M-R**
- 32 x IR receiver cables (marked IR RX) **NOT UTILIZED IN THIS PACKAGE**
- 32 x 5VDC power supply
- 32 x rack mounting brackets.
- 1 x Operating instructions.
- 1 x CD with RS232 commands and control