Apantac T#-64x4-4RU-S 4 RU 64x4 3G/HD/SD-SDI/CVBS I/O Multiviewer w UOM-SFP-A

64 input quad head multiviewer. 4 RU. Accepts 40 3G/HD/SD-SDI/CVBS video inputs. All inputs can be shared on all 4 outputs. Output up to 1600x1200 / 1920x1080 / 1920x1200 @ 50/60Hz. Equipped with five VSM-SDI + UIM-SDI, one OPM-A + UOM-SFP-A and redundant power supplies.

Features

- Inputs: Up to 64 3G/HD/SD-SDI, composite video, fiber
- HDMI and IP input boards coming soon
- Pre-configured Multiviewers available OR configure your own Multiviewer - hot pluggable IO boards
- Outputs: Up to 8 outputs on 4 RU frame, up to 4 outputs on 2 RU and 1 RU frames
- Output formats: Fiber, SDI, HDMI, HDMI extenders, HDBaseT extenders
- Output resolutions: 1920x1200 including 1080P
- Image duplication - all inputs can be duplicated up to 64 times on a single display
- 4K/UHD output ready
- 16 channels of embedded audio per SDI input
- Supports 3rd party routers, production switchers
- Apantac Skin Technology - labels, borders, clocks & logos, tally & GPI/O, alarms, audio meters
- 3 frame sizes available
- 3 year warranty
- Cost-effective