

Atlona AT-RGB1624-A Atlona 16x24 Professional RGBHV with Audio Matrix Switch

Atlona 16x24 Professional RGBHV with Audio Matrix Switch. Model: AT-RGB1624-A

The Atlona AT-RGB1624-A is an 16 input 24 output Commercial RGBHV with Audio matrix switcher. The AT-RGB1624-A is one of the world's advanced matrix switchers. It is capable of being controlled through RS232 via software included or via a third party control system. Switcher is designed to handle any resolution up to UXGA (1600x1200) without any signal degradation. The switcher is capable of routing audio signals in a different matrix than video if applicable.

This device is mainly used in broadcast room, multi council-chamber, television teaching room and command center.

Main Features:

- Power-Fail Protection, allows switcher to restore previous settings
- LCD display, shows all programmed commands and switcher responses
- Preset ability, allows user to save specific tasks under one of the 10 presets and call it back with shortcut
- RS232 Communication Control Input, allows to control switcher via included advanced Control software or Third Party Control System
- IR Remote Control
- Audio and Video could have a separate matrix modes (Example: Video in 1 ---> Video Out 2, while Audio in 1---> Audio Out 3)
- Inputs: 16 x RGBHV female(5-BNC female per input); 16 x screw audio terminals for balanced or unbalanced audio (Phoenix Connectors)
- Outputs: 24 x RGBHV female (5-BNC female per output); 24 x screw audio terminals for balanced or unbalanced audio (Phoenix Connectors)
- Connectors: RGBHV (BNC style) (Could be used for PC resolutions up to UXGA - 1600x1200 or HDTV up to 1080p)
- Compatible Formats: RGBHV, YPrPb, RGB, Composite
- Lock Safe, allows user to lock unit from being accidentally switched to incorrect mode
- Undo Function, allows user to undo the incorrect operation and return to the previous setting
- Standard 19" x 3" Rack Mount Size - 10U

Technical Specifications:

- High Resolution Support: up to 1600x1200@85Hz or even higher
- Bandwidth: 450MHz @ (-3dB), fully loaded @1600x1200@85Hz or higher
- Cross talk sum: 56dB @10M, -40dB @100M
- Switching speed: 200 ns (Max)
- Signal type: RGB, YPrPb, RGBHV, RGBS, RGSB, RsGsBs, Component, Composite
- Audio Connectors: screw audio terminals for balanced or unbalanced audio (Phoenix Connectors)
- Echo Loss: <-40dB@5MHz
- Audio Frequency: 20 Hz to 20 kHz
- Standard 19" x 3" Rack Mount Size -10U
- Connector: BNC female (5-BNC per input/output)
- Communication Port: RS232
- Impedance: 75 Ohm
- Temperature: 20C to +70C (-20 F to 158 F)
- Power Supply: 110V-240V (50-60Hz)
- Dimensions (mm): W 485 X H 443 X D 266
- Dimensions (inch): W 19 X H 17.44 X D 10.47
- Unit Weight: 12.5kg or 25LB
- Gross Package Weight: 28LB

Package Includes:

- 1 x AT-RGB2416-A
- 1 x RS-232 Communication Cord
- 1 x Power Supply Cord (US)
- 1 x CD with RS232 Application Software
- 1 x IR Remote
- 40 x Phoenix Connectors for Audio
- 1 x User's Manual and Quality Guarantee

Warranty:

2 year manufacturer's warranty (parts and labor)